

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone;

a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising:

steel in the range of from 20 to 50 percent by weight; and

filler in the range of from 50 to 80 percent by weight,

the filler comprising in the range of from 10 to 100 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 16 to 40 mesh and between about 80 and 200 mesh, and tungsten carbide particles selected from the group consisting of spherical cemented, crushed cemented, crushed cast, crushed macrocrystalline, and carburized.

4. (Amended) The rock bit of claim 1 wherein the filler comprises in the range of from 40 to [99] 100 percent by weight spherical cast tungsten carbide particles.

7. (Amended) The rock bit of claim [6] 1 wherein the filler comprises spherical cast tungsten carbide particles having [a] particle [size] sizes between about 100 to 200 mesh.

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

8. (Amended) The rock bit of claim [5] 1 wherein the filler further comprises macrocrystalline tungsten carbide particles having [a] particle [size] sizes between about 40 to 80 mesh.

3
9. (Amended) A rock bit as recited in claim 1 wherein the hardfacing comprises in the range of from 10 to 90 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 16 to 40 mesh, and further comprises ultra-fine tungsten carbide particles in the range of from 10 to 35 percent by weight of the filler material, the particles having [a] particle [size] sizes in the range of from about 1 to 50 microns.

12. (Amended) A rock bit comprising:

a body;

at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone;

4
a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising:

steel in the range of from 20 to 50 percent by weight;

filler in the range of from 50 to 80 percent by weight,

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

① the filler comprising in the range of from 10 to 100 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 80 to 200 mesh.

16. (Amended) The rock bit of claim 12 wherein the filler comprises spherical cast tungsten carbide particles having [a] particle [size] sizes between about 100 to 200 mesh.

⑤ 17. (Amended) The rock bit of claim 12 wherein the filler comprises in the range of from 10 to 99 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 80 to 200 mesh, and further comprises spherical cast tungsten carbide particles having [a] particle [size] sizes between about 16 to 40 mesh.

① 18. (Amended) The rock bit of claim 12 wherein the filler comprises in the range of from 10 to 99 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 80 to 200 mesh, and further comprises tungsten carbide particles selected from the group including spherical cemented, crushed cemented, crushed cast and crushed macrocrystalline.

19. (Amended) The rock bit of claim 18 wherein the filler further comprises macrocrystalline tungsten carbide particles having [a] particle [size] sizes between about 40 to 80 mesh.

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

5
20. (Amended) A rock bit as recited in claim 12 wherein the hard-facing comprises in the range of from 10 to 90 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 80 to 200 mesh, and further comprises ultra-fine tungsten carbide particles in the range of from 10 to 35 percent by weight of the filler material, the particles having a particle size in the range of from about 1 to 50 microns.

23. (Amended) A rock bit comprising:

a body;

at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone;

6
a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising:

steel in the range of from 20 to 50 percent by weight;

filler in the range of from 50 to 80 percent by weight, the filler comprising in the range of from 10 to 100 percent by weight spherical cast tungsten carbide particles having [a] particle [size] sizes between about 16 to 40 mesh and between about 80 to 200 mesh.

24. (Amended) A rock bit as recited in claim 23 wherein the hard-facing comprises in the range of from 10 to 90 percent by weight spherical cast tungsten carbide particles having [a]

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

6
D
particle [size] sizes between about 16 and 40 mesh and between about 80 to 200 mesh, and further comprises ultra-fine tungsten carbide particles in the range of from 10 to 40 percent by weight of the filler material, the particles having [a] particle [size] sizes in the range of from about 1 to 50 microns.

27. (Amended) The rock bit of claim 23 wherein the filler comprises spherical cast tungsten carbide particles having [a] particle [size] sizes between about 100 to 200 mesh.

28. (Amended) A rock bit comprising:

a body;

7
D
at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone; and

a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising,

steel, and

filler in the range of from 50 to 80 percent by weight, the filler comprising in the range of from 10 to 100 percent by weight spherical cast tungsten carbide particles having particle sizes between about 16 mesh to less than 40 mesh.

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

29. (Amended) A rock bit as recited in claim 28 wherein the filler comprises in the range of from 19 to 100 percent by weight spherical cast tungsten carbide particles.

30 31. (Amended) A rock bit as recited in claim 28 further comprising spherical tungsten carbide particles having particle sizes between greater than 80 to 200 mesh.

31 32. (Amended) A rock bit comprising:
a body;
at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone; and
a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising,
steel, and
filler in the range of from 50 to 80 percent by weight, the filler comprising in the range of from 10 to 100 percent by weight spherical cast tungsten carbide particles having particle sizes between greater than 80 mesh and 200 mesh.

32 33. (Amended) A rock bit as recited in claim 32 wherein the filler comprises in the range of from 19 to 100 percent by weight spherical cast tungsten carbide particles.

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

31

33 35. (Amended) A rock bit as recited in claim 32 further comprising spherical tungsten carbide particles having particle sizes between 16 to less than 40 mesh.

34 36. (Amended) A rock bit comprising:

a body;

at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone; and

a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising,

steel, and

filler in the range of from 50 to 80 percent by weight, the filler comprising in the range of from 10 to 100 percent by weight spherical cast tungsten carbide particles having particle sizes between about 16 to 40 mesh and between about 80 to 200 mesh.

36

35 37. (Amended) A rock bit as recited in claim 36 comprising steel in the range of 20 to 50 percent by weight, and wherein the spherical tungsten carbide particles have particle sizes between about 16 to less than 40 mesh and between greater than 80 to 200 mesh.

36 38. (Amended) A rock bit comprising:

a body;

Appln No. 09/637,764

Amdt date December 9, 2003

Reply to Office action of June 26, 2003

at least one cutting cone rotatably mounted to an end of the body, wherein the cone includes a gage surface at a heel portion of the cone; and

a number of teeth on the cone, the teeth including a plurality of inner row teeth and a plurality of gage row teeth located near a heel of each cone, wherein the teeth include a hardfacing comprising,

steel, and

filler in the range of from 50 to 80 percent by weight, the filler comprising in the range of from (19 to 100) percent by weight spherical cast tungsten carbide particles.

whole
in
spec.

37

40. (Amended) A rock bit as recited in claim 28 wherein the filler comprises in the range of from 19 to 100 percent by weight spherical cast tungsten carbide.

3,

38

41. (Amended) A rock bit as recited in claim 38 wherein the filler comprises in the range of from 19 to 100 percent by weight spherical cast tungsten carbide.